

1033-E

9.9" Resizing LCD, 700 nits LED backlight, 800x200



Key Features

- 9.9" resizing LCD
- Resizing display (aspect ratio of 16:4)
- Brightness of 700 nits
- Resolutions: 800 x 200
- Low power consumption
- BL MTBF: 70,000 hours

Specifications

	SSF1033-E	SSH1033-E	SSD1033-E
Description	9.9" Resizing LCD, 700 nits LED backlight, 800x200		
Screen size	9.9"		
Display area (mm)	246.6(H) x 61.5(V)		
Brightness	700 cd/m ²		
Resolution	800x200		
Aspect ratio	16:4		
Contrast ratio	600:1		
Pixel pitch (mm)	0.3075 (H) x 0.3075 (V)		
Pixel per inch (PPI)	82		
Viewing angle	160° (H), 135° (V)		
Color saturation (NTSC)	66%		
Display colors	262K		
Response time (Typical)	35ms		
Video interface	LVDS	VGA, CBVS, S-Video	
Input power		DC 12V	
Power consumption	3.8W	9.6W	
Dimensions (mm)	279x87.1x9	279x87.1x9	291x106.2x46.2
Bezel size (U/B/L/R)	13.85/6.85/16/13.95	13.85/6.85/16/13.95	21.3/21.3/22.05/22.05
Weight (Net)	0.25kg	0.38kg	1.2kg
Mounting			VESA 75x75
OSD key		4 keys (Power switch, menu, +, -)	
OSD control		Brightness, color, contrast, H/V position... etc	
Operating temperature	-20°C ~ +70°C		
Storage temperature	-30°C ~ +80°C		
Product approval			CE, FCC

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

Ordering Information

SSF1033-ENN-A01	9.9", 700nits, 800*200, LID on module, 5 in 1, V1
SSH1033-ENN-G01	9.9", 700nits, 800*200, AD2662GVA, 5 in 1, V1
SSD1033-ENB-G01	9.9", 700nits, 800*200, AD2662GVA, O/B, DC 12V input, 1 in 1, V1