

1945-M

19.4" TFT LCD, 1000 nits LED backlight, MaxRGB, 1920x536



Key Features

- 19.4" resizing LCD
- Resizing display (aspect ratio of 16:4.5)
- Sunlight readable, high brightness (1,000nits)
- Resolutions: 1920 x 536
- MaxRGB (NTSC 92%)
- Wide view angle of 178° (H), 178° (V)
- BL MTBF: 100,000 hours

Specifications

	SSF1945-M	SSH1945-M	SSD1945-M
Description	19.4" TFT LCD, 1000 nits LED backlight, MaxRGB, 1920x536		
Screen size	19.4"		
Display area (mm)	476.06(H) x 132.9(V)		
Brightness	1000 cd/m ²		
Resolution	1920x536		
Aspect ratio	16:4.5		
Contrast ratio	6000 : 1		
Pixel pitch (mm)	0.248(H) x 0.248(V)		
Pixel per inch (PPI)	102		
Viewing angle	178°(H),178°(V)		
Color saturation (NTSC)	92%		
Display colors	16.7M		
Response time (Typical)	20ms		
Video interface	LVDS	DP	
Input power		DC 12V	
Power consumption	21.5W	23W	
Dimensions (mm)	497x149.8x13.31	497x149.8x13.31	499.6x 152.3 x 31.8
Bezel size (U/B/L/R)	9.6/5.14/8.68/8.68	9.6/5.14/8.68/8.68	10.8/6.44/9.98/9.98
Weight (Net)	0.92kg	0.95kg	1.9kg
Mounting			N/A
OSD key		4 keys (Power switch, menu, +, -)	
OSD control		Brightness, Color, Contrast, Auto Turing, H/V Position...etc	
Operating temperature	0 °C ~ +50 °C		
Storage temperature	-20 °C ~ 60 °C		
Product approval			

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

Ordering Information

SSF1945-MNW-A01	19.4", 1000nits, 1920*536, MaxRGB, LID19C, 10in1, V1
SSH1945-MNW-Q01	19.4", 1000nits, 1920*536, MaxRGB, AD8891P w/LID, DC12V, 10in1, V1
SSD1945-MNW-Q01	19.4", 1000nits, 1920*536, MaxRGB, AD8891P w/LID, O/B, DC12V, 5in1, V1