

2906-Y

29" TFT LCD, 1200 nits LED backlight, 1920x540



Sunlight Readable



Stretched Display



Blanking Defect Free



MTBF

100,000 Hrs



Key Features

- 29" stretched LCD
- Stretched display (aspect ratio of 16 : 4.5)
- Sunlight readable, high brightness (1,200 nits)
- Resolutions: 1920 x 540
- LCD blanking defect free (Hi-Tni 110°C)
- Low power consumption
- BL MTBF: 100,000 hours

Specifications

	SSF2906-Y	SSH2906-Y	SSD2906-Y
Description	29" TFT LCD, 1200 nits LED backlight, 1920x540		
Screen size	29"		
Display area (mm)	698.4(H) x 196.4(V)		
Brightness	1200 cd/m ²		
Resolution	1920 x 540		
Aspect ratio	16:4.5		
Contrast ratio	1200:1		
Pixel pitch (mm)	0.36375(H) x 0.36375(V)		
Pixel per inch (PPI)	70		
Viewing angle	178°(H),178°(V)		
Color saturation (NTSC)	80%		
Display colors	16.7M		
Response time (Typical)	25ms		
Video interface	LVDS	DVI-I, HDMI, DP	
Input power		DC 12V	
Power consumption	54.26W	55W	
Dimensions (mm)	731.46x 229.49 x 20.34	731.46x 229.49 x 20.34	734.5x 232.5 x 60.1
Bezel size (U/B/L/R)	14.53/14.53/14.53/14.53	14.53/14.53/14.53/14.53	16/16/16/16
Weight (Net)	2.7kg	2.9kg	5.8kg
Mounting			VESA 400x75, 75x75
OSD key		4 keys (Power switch, menu, +, -)	
OSD control		Brightness, Color, Contrast, Auto Turing, H/V Position...etc	
Operating temperature	0°C ~ +50°C		
Storage temperature	-20°C ~ +60°C		
Product approval			CE, FCC

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

Ordering Information

SSF2906-YNN-A11	29", 1200nits, 1920*540, HTni, LID29C, 5in1, V2
SSH2906-YNN-Q11	29", 1200nits, 1920*540, HTni, LID29C, AD8891GDHP, DC12V, 5in1, V2
SSD2906-YNB-Q11	29", 1200nits, 1920*540, HTni, LID29C, AD8891GDHP, O/B, DC12V, 3in1, V2