



3685-I

36.8" Resizing LCD, 1000 nits LED backlight, 1920x358



Key Features

- 36.8" resizing LCD
- Resizing display (aspect ratio of 16 : 2.9)
- Sunlight readable, high brightness (1,000 nits)
- Resolutions: 1920 x 358
- Wide view angle of 178° (H), 178° (V)
- Low power consumption
- BL MTBF: 100,000 hours

Specifications

	SSF3685-I	SSH3685-I	SSD3685-I
Description	36.8" Resizing LCD, 1000 nits LED backlight, 1920x358		
Screen size	36.8"		
Display area (mm)	919.3(H) x 171.4(V)		
Brightness	1000 cd/m ²		
Resolution	1920x358		
Aspect ratio	16:2.9		
Contrast ratio	7600:1		
Pixel pitch (mm)	0.4788 (H) x 0.4788 (V)		
Pixel per inch (PPI)	52		
Viewing angle	178° (H), 178° (V)		
Color saturation (NTSC)	81%		
Display colors	16.7M		
Response time (Typical)	9.5ms		
Video interface	LVDS	VGA, DVI-D, HDMI	
Input power		DC 12V	
Power consumption	22W	27W	
Dimensions (mm)	960x207.3x16	960x207.3x16	962.8x210.1x56.2
Bezel size (U/B/L/R)	15.2/15.2/17.8/17.8	15.2/15.2/17.8/17.8	16.6/16.6/19.2/19.2
Weight (Net)	3.5kg	3.8kg	6.3kg
Mounting			VESA 75x75, 400x75
OSD key		4 keys (Power switch, menu, +, -)	
OSD control		Brightness, color, contrast, H/V position... etc	
Operating temperature	0°C ~ +50°C		
Storage temperature	-20°C ~ +60°C		
Product approval			CE, FCC

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

Ordering Information

SSF3685-INN-A01	36.8", 1000nits, 1920*358, LID36A, 2in1, V1
SSH3685-INN-G01	36.8", 1000nits, 1920*358, LID36A, AD2662GDHMVAR, DC12V, 2in1, V1
SSD3685-INB-G01	36.8", 1000nits, 1920*358, LID36A, AD2662GDHM, O/B, DC12V, 2in1, V1